

ARCHITECTURAL USL-SRD3Q Myrtle Suspended Pendant



PROJECT		TYPE		DATE	
---------	--	------	--	------	--










Architectural Interior Damp Location Dimmable AC Down Light 5 Year Warranty

OVERVIEW

The Myrtle pendant is rectangular with down light. It comes standard with 0-10V dimming; TRIAC and DALI are optional. Available as single rings or tiers of 2-5 rings.



FEATURES

- Damp location
- 160° beam angle
- Direct lights
- Can group 2-5 tiers together
- IP20
- 0-10V dimming

ORDERING INFORMATION

EXAMPLE PN: USL-SRD3Q-16X32-50W-50K-TRIAC-8016

USL-SRD3Q	SIZE / POWER	CCT	DIMMING	FINISH
	8X16-25W 8X16 INCH 25 WATTS	30K 3000K	10V 0-10V	W WHITE
	12X24-40W 12X24 INCH 40 WATTS	35K 3500K	TRI TRIAC	B BLACK
	16X32-50W 16X32 INCH 50 WATTS	40K 4000K		S SILVER
	24X40-80W 24X40 INCH 80 WATTS	50K 5000K		#### CUSTOM RAL (ENTER CODE)

ARCHITECTURAL USL-SRD3Q Myrtle Suspended Pendant



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SRD3Q	120-277V	-4°F – 104°F -20°C – 40°C	50,000 HOURS	3000K, 3500K, 4000K, 5000K	90+	64-70 lm/W

MODEL	POWER (W)	SIZE	LUMENS (lm) ±10%				EFFICACY (lm/W)
			3000K	3500K	4000K	5000K	
USL-SRD3Q-8X16-25W	25	8x16	1,597	1,647	1,698	1,750	64-70
USL-SRD3Q-12X24-40W	40	12x24	2,555	2,635	2,716	2,800	64-70
USL-SRD3Q-16X32-50W	50	16x32	3,194	3,293	3,395	3,500	64-70
USL-SRD3Q-24X40-80W	80	24x40	5,111	5,269	5,432	5,600	64-70

DIMENSIONS

MODEL	L LENGTH	W WIDTH
USL-SRD3Q-8X16-25W	7.9 in 200 mm	15.7 in 400 mm
USL-SRD3Q-12X24-40W	11.8 in 300 mm	23.6 in 600 mm
USL-SRD3Q-16X32-50W	15.7 in 400 mm	31.5 in 800 mm
USL-SRD3Q-24X40-80W	23.6 in 600 mm	39.4 in 1000 mm