

EXTERIOR USL-FWP1A Full Cutoff Wall Pack



PROJECT	TYPE	DATE
---------	------	------

Exterior Location
 Non-Dimming Dimmable
 10V
 AC
 Down Light
 5 Year Warranty
 DLC
 UL
 IES

OVERVIEW

This full-cutoff wall pack is ideal for use in perimeter and security lighting, walkways, and entrances while preventing unwanted light from going elsewhere. The fixture is suitable for applications requiring 3G testing prescribed by ANSI C136.31.

Select models are dimmable. Please see specification table for details.



FEATURES

- Cast aluminum body
- PF > 0.9
- THD < 20%
- Select models are 0-10V dimmable



ORDERING INFORMATION

EXAMPLE PN: USL-FWP1A-70W-LV-40K-D-0-0

USL-FWP1A	POWER ^{[1] [3]}	VOLTAGE ^{[1] [2] [3]}	CCT	FINISH	OPTIONS ^[2]	DIMMING ^[3]
	27W 27 WATTS	LV 120-277V	40K 4000K	D DARK BRONZE	0 NO PHOTOCELL	0 NON DIMMING
	45W 45 WATTS	HV 347-480V	50K 5000K	B BLACK	PO 120-277V PHOTOCELL	10V 0-10V DIMMING
	70W 70 WATTS			W WHITE		
	90W 90 WATTS					
	135W 135 WATTS					

[1] Note: 27W only available with 120-277V

[2] Note: 347-480V not available with photocell

[3] Note: Dimming not available on all models. 90W-LV and all HV models are dimmable

EXTERIOR USL-FWP1A

Full Cutoff Wall Pack



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-FWP1A	120-277V AC 347-480V AC	-40°F – 113°F -40°C – 45°C	50,000 HOURS	4000K, 5000K	70+	133-146 lm/W

MODEL	POWER (W)	DIMMABLE MODELS		LUMENS (lm) ±10%		EFFICACY (lm/W)
		LV	HV	4000K	5000K	
USL-FWP1A-27W	27	–	✓	3,900	3,950	144-146
USL-FWP1A-45W	45	–	✓	6,400	6,450	142-143
USL-FWP1A-70W	70	–	✓	9,800	9,900	140-141
USL-FWP1A-90W	90	✓	✓	12,000	12,200	133-136
USL-FWP1A-135W	135	–	✓	18,000	18,000	133-133

DIMENSIONS

MODEL	W WIDTH	H HEIGHT	D DEPTH	WEIGHT
USL-FWP1A-27W	14.21 in 361 mm	9.25 in 235 mm	7.99 in 203 mm	5.77 lb
USL-FWP1A-45W				5.98 lb
USL-FWP1A-70W				6.16 lb
USL-FWP1A-90W	18.096 in 459.95 mm	9.75 in 247.65 mm	9.02 in 228.98 mm	10.478 lb
USL-FWP1A-135W				10.95 lb

