

# INTERIOR USL-T5DL2E Slim Strip Light



Interior Warranty

## OVERVIEW

This T5 replacement fixture contains an integrated heat sink for improved thermal conductivity. Multiple segments can be hooked together (up to 200W) to create longer lengths using either a cable or seamless connector.

## FEATURES

- Seamless connection option
- THD<19%
- PF>0.92
- 120° beam angle
- Aluminum body



## ORDERING INFORMATION

EXAMPLE PN: USL-T5DL2E-900-12W-40K-F

USL-T5DL2E	SIZE / POWER	CCT	LENS
<b>600-7W</b>	2 FT, 7W	<b>30K</b> 3000K	<b>C</b> CLEAR
<b>900-12W</b>	3 FT, 12 W	<b>40K</b> 4000K	<b>F</b> FROSTED
<b>1200-15W</b>	4 FT, 15 W	<b>50K</b> 5000K	
<b>1500-20W</b>	5 FT, 20W	<b>60K</b> 6000K	
<b>1800-22W</b>	6 FT, 22W		
<b>2400-30W</b>	8 FT, 30W		

\*Note: only 2, 3, 4, 5 foot models are DLC-listed

## ACCESSORIES

USL-T5DL2E-ACC	ACCESSORY
<b>SUSPKIT</b>	Suspension kit, 2 pieces, 1m standard length

# INTERIOR USL-T5DL2E Slim Strip Light



## SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-T5DL2E	100-277V AC	-4°F – 50°F -20°C – 50°C	50,000 HOURS	3000K, 4000K, 5000K, 6000K	80+	105-110 lm/W

MODEL	POWER (W)	LUMENS - FROSTED (lm)	LUMENS - CLEAR (lm)	EFFICACY (lm/W)	DLC
USL-T5DL2E-600-7W	7	735	770	105-110	✓
USL-T5DL2E-900-12W	12	1,260	1,320	105-110	✓
USL-T5DL2E-1200-15W	15	1,575	1,650	105-110	✓
USL-T5DL2E-1500-20W	20	2,100	2,200	105-110	✓
USL-T5DL2E-1800-22W	22	2,310	2,420	105-110	N
USL-T5DL2E-2400-30W	30	3,150	3,300	105-110	N

## DIMENSIONS

MODEL	L	W	H
<b>USL-T5DL2E-600-7W</b>	23.62 in 600 mm	1.1 in 28 mm	1.5 in 38 mm
<b>USL-T5DL2E-900-12W</b>	35.43 in 900 mm	1.1 in 28 mm	1.5 in 38 mm
<b>USL-T5DL2E-1200-15W</b>	42.24 in 1200 mm	1.1 in 28 mm	1.5 in 38 mm
<b>USL-T5DL2E-1500-20W</b>	59.05 in 1500 mm	1.1 in 28 mm	1.5 in 38 mm
<b>USL-T5DL2E-1800-22W</b>	70.86 in 1800 mm	1.1 in 28 mm	1.5 in 38 mm
<b>USL-T5DL2E-2400-30W</b>	94.48 in 2400 mm	1.1 in 28 mm	1.5 in 38 mm

