

INTERIOR USL-FPC3H RGB Flat Panel



PROJECT	TYPE	DATE
---------	------	------



OVERVIEW

This RGB/RGBW fixture is available in multiple sizes: 1x1, 1x2, 1x4, 2x2, and 2x4. It is can be used with controls including DMX, DALI, Zigbee, and wifi.

FEATURES

- Multiple sizes available
- RGB and RGBW models
- Works with DMX, DALI, Zigbee, or wifi
- RGBW available with 3000K, 4000K, 5000K, 6000K



ORDERING INFORMATION

EXAMPLE PN: USL-FPC3H-1X1-18W-LV-RGB-DMX

USL-FPC3H	SIZE / POWER	VOLTAGE	CCT/COLOR	CONTROLS
	1X1-18W 1X1, 18 WATTS	LV 110-270V	RGB RGB	DMX DMX
	1X2-40W 2X2, 40 WATTS		RGB30 RGBW (3000K)	DALI DALI
	2X2-40W 2X2, 40 WATTS		RGB40 RGBW (4000K)	ZGB ZIGBEE
	1X4-40W 1X4, 40 WATTS		RGB50 RGBW (5000K)	WIFI WIFI
	2X4-54W 2X4, 54 WATTS		RGB60 RGBW (6000K)	

INTERIOR USL-FPC3H RGB Flat Panel



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	EFFICACY
USL-FPC3H	110-270V	-4°F – 104°F -20°C – 40°C	50,000 HOURS	RGB, RGBW	50 lm/W

MODEL	POWER (W)	LUMENS (lm) ±10%	lm/ft ²	EFFICACY (lm/W)
USL-FPC3H-1X1-18W	18	900	900	50
USL-FPC3H-1X2-40W	40	2,000	1,000	50
USL-FPC3H-2X2-40W	40	2,000	500	50
USL-FPC3H-1X4-40W	40	2,000	500	50
USL-FPC3H-2X4-54W	54	2,700	338	50

DIMENSIONS

MODEL	L LENGTH	W WIDTH	T THICKNESS	WEIGHT
1X1-18W	11.614 in 295 mm	11.614 in 295 mm	0.472 in 12 mm	5.5 lb 2.5 kg
1X2-40W	23.425 in 595 mm	11.614 in 295 mm		7.1 lb 3.2 kg
2X2-40W	23.425 in 595 mm	23.425 in 595 mm		22.7 lb 10.3 kg
1X4-40W	47.05 in 1195 mm	11.614 in 295 mm		9.9 lb 4.5 kg
2X4-54W	47.05 in 1195 mm	23.425 in 595 mm		11.5 lb 5.2 kg

