

ARCHITECTURAL USL-SRU3Q Phalen Suspended Pendant



PROJECT		TYPE		DATE	
---------	--	------	--	------	--










Architectural Interior Damp Location Dimmable AC Up/Down Warranty

OVERVIEW

The Phalen pendant is rectangular with up/down light. It comes standard with 0-10V dimming; TRIAC and DALI are optional. Available as single rings or tiers of 2-5 rings.



FEATURES

- Damp location
- 280° beam angle
- Direct & indirect lights
- Can group 2-5 tiers together
- IP20
- 0-10V dimming

ORDERING INFORMATION

EXAMPLE PN: USL-SRU3Q-24X40W-30K-10V-B

USL-SRD3Q	SIZE / POWER	CCT	DIMMING	FINISH
	8X16-50W 8X16 INCH 50 WATTS	30K 3000K	10V 0-10V	W WHITE
	12X24-80W 12X24 INCH 80 WATTS	35K 3500K	TRI TRIAC	B BLACK
	16X32-100W 16X32 INCH 100 WATTS	40K 4000K		S SILVER
	24X40-160W 24X40 INCH 160 WATTS	50K 5000K		### CUSTOM RAL (ENTER CODE)

ARCHITECTURAL USL-SRU3Q Phalen Suspended Pendant



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SRU3Q	120-277V	-4°F – 104°F -20°C – 40°C	50,000 HOURS	3000K, 3500K, 4000K, 5000K	90+	64-70 lm/W

MODEL	POWER (W)	SIZE	LUMENS (lm) ±10%				EFFICACY (lm/W)
			3000K	3500K	4000K	5000K	
USL-SRU3Q-8X16-50W	50	8x16	3,194	3,293	3,395	3,500	64-70
USL-SRU3Q-12X24-80W	80	12x24	5,111	5,269	5,432	5,600	64-70
USL-SRU3Q-16X32-100W	100	16x32	6,389	6,586	6,790	7,000	64-70
USL-SRU3Q-24X40-160W	160	24x40	10,222	10,538	10,864	11,200	64-70

DIMENSIONS

MODEL	L LENGTH	W WIDTH
USL-SRU3Q-8X16-50W	7.9 in 200 mm	15.7 in 400 mm
USL-SRU3Q-12X24-80W	11.8 in 300 mm	23.6 in 600 mm
USL-SRU3Q-16X32-100W	15.7 in 400 mm	31.5 in 800 mm
USL-SRU3Q-24X40-160W	23.6 in 600 mm	39.4 in 1000 mm