

# INTERIOR USL-HBL21D

## Linear High Bay



PROJECT	TYPE	DATE
---------	------	------



Interior



Dimmable



AC



Down Light



Warranty



### OVERVIEW

This linear high bay is available in 2-foot and 4-foot lengths. Electronics and optics are separated to lower fixture temperatures, extending the lifespan.

### FEATURES

- Modular design
- 105° beam angle
- PF > 0.9
- Bi-level dimming



### ORDERING INFORMATION

EXAMPLE PN: USL-HBL21D-4-4-160W-LV-40K-10V

USL-HBL21D	SIZE / POWER	VOLTAGE	CCT	OPTIONS
	<b>2-4-100W</b> 2 FT 4 MODULES 100 WATTS	<b>LV</b> 120-277V	<b>30K</b> 3000K	<b>10V</b> 0-10V DIMMING
	<b>2-6-160W</b> 2 FT 6 MODULES 160 WATTS	<b>HV</b> 347-480V	<b>35K</b> 3500K	<b>MS</b> MOTION SENSOR
	<b>4-4-160W</b> 4 FT 4 MODULES 160 WATTS		<b>40K</b> 4000K	
	<b>4-4-200W</b> 4 FT 4 MODULES 200 WATTS		<b>50K</b> 5000K	
	<b>4-6-240W</b> 4 FT 6 MODULES 240 WATTS			
	<b>4-6-300W</b> 4 FT 6 MODULES 300 WATTS			

# INTERIOR USL-HBL21D Linear High Bay



## SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-HBL21D	120-277V 347-480V	-40°F – 131°F -40°C – 55°C	60,000 HOURS	3000K, 3500K, 4000K, 5000K	80+	130-140 lm/W

MODEL	POWER (W)	LENGTH	MODULES	LUMENS (lm) ±10%				EFFICACY (lm/W)
				3000K	3500K	4000K	5000K	
USL-HBLID-2-4-100W	100	2 ft	4	13,000	13,500	13,700	13,700	130-137
USL-HBLID-2-6-160W	160		6	21,000	21,600	22,400	22,450	131-140
USL-HBLID-4-4-160W	160	4 ft	4	20,800	21,600	22,200	22,300	130-139
USL-HBLID-4-4-200W	200			26,000	27,000	27,000	27,600	130-138
USL-HBLID-4-6-240W	240		6	31,200	32,400	33,000	33,400	130-139
USL-HBLID-4-6-300W	300			39,000	40,000	40,500	40,800	130-136

## DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT	WEIGHT
USL-HBLID-2-4-100W	23.6 in 600 mm	9.84 in 250 mm	1.7 in 43 mm	3.2 in 7 kg
USL-HBLID-2-6-160W		13.4 in 340 mm		3.4 in 7.6 kg
USL-HBLID-4-4-160W	46.7 in 1185 mm	9.84 in 250 mm		5.8 in 12.8 kg
USL-HBLID-4-4-200W				5.9 in 13 kg
USL-HBLID-4-6-240W		13.4 in 340 mm		6.8 in 15 kg
USL-HBLID-4-6-300W				6.9 in 15.2 kg

