



OVERVIEW

This corn bulb retrofit features an external driver for thermal driver eliminating the need for a fan. Uplight is eliminated to reduce light pollution. Multiple mounting options are available to fit a variety of application needs.

FEATURES

- External driver for thermal management
- Fan-less design
- Dark Sky
- Available with E26 and E39 socket



ORDERING INFORMATION

EXAMPLE PN: USL-RT21H-40W-45K-E39-0-0

USL-RT21H	POWER ^[1] ^[2]	CCT	MOUNTING ^[1] ^[3]	PHOTOCELL	DIMMING ^[2]
	15W 15 WATTS	40K 4000K	XB X BRACKET	0 NONE	0 NONE
	22W 22 WATTS	45K 4500K	E39 E39	P PHOTOCELL	10V DIMMING
	40W 40 WATTS	50K 5000K	E26 E26		
	56W 56 WATTS		E26/E39 E26 AND E39		

^[1]Note: X-bracket required for DLC with 15/22W

^[2] Dimming is not DLC for 15/22/40W

^[3] E26 is not DLC-listed

*Note: All configurations are ETL-listed, but not all combinations are DLC-listed. See certifications table below for more information.

DLC CERTIFICATIONS

POWER (W)	X BRACKET	E39	E26	DIMMING	PHOTOCELL	PHOTOCELL + DIMMING
USL-RT21H-15W	✓	N	N	N	✓	N
USL-RT21H-22W	✓	N	N	N	✓	N
USL-RT21H-40W	✓	✓	N	N	✓	N
USL-RT21H-56W	N	✓	N	✓	✓	✓

SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-RT21H	100-277V	-31°F – 131°F -35°C – 55°C	100,000 HOURS	4000K, 4500K, 5000K	70+	87-93 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)	REPLACE MH
USL-RT21H-15W	15	1,339	89	40W
USL-RT21H-22W	22	2,044	93	60W
USL-RT21H-40W	40	3,562	89	100W
USL-RT21H-56W	56	4,862	87	150W

DIMENSIONS

MODEL	D DIAMETER	L LIGHT HEIGHT	H ₁ HEIGHT E39	H ₂ HEIGHT X BRACKET
15/22W	3.93 in 100 mm	3.0 in 75 mm	7.69 in 195 mm	5.34 in 136 mm
40W	3.93 in 100 mm	4.72 in 120 mm	9.4 in 240 mm	7.05 in 179 mm
56W	3.86 in 98 mm	5.9 in 150 mm	10.58 in 269 mm	9.12 in 232 mm

