

INTERIOR USL-HBF2E Flexible High Bay



Interior



Non-Dimming



Dry
Location



5
Year
Warranty



OVERVIEW

This high bay is composed of 3-7 modular segments separated by hinges. This allows the lighting surface of the fixture to be adjusted by flexing the fixture either concave or convex.



FEATURES

- Power entry from the back
- Modular, segmented design
- Hinged design
- Aluminum body and polycarbonate lens
- 2-foot and 4-foot models
- Frosted lens
- Internal driver



ORDERING INFORMATION

EXAMPLE PN: USL-HBF2E-2-45W-40K-180D

USL-HBF2E	SIZE / POWER	CCT	BEAM ANGLE
	2-45W 2 FEET, 45 WATTS 3 PIECES	30K 3000K	60D 60 DEGREES
	2-75W 2 FEET, 75 WATTS 5 PIECES	40K 4000K	120D 120 DEGREES
	2-105W 2 FEET, 105 WATTS 7 PIECES	50K 5000K	180D 180 DEGREES
	4-90W 4 FEET, 90 WATTS 3 PIECES	60K 6000K	
	4-150W 4 FEET, 150 WATTS 5 PIECES		
	4-210W 4 FEET, 210 WATTS 7 PIECES		

INTERIOR USL-HBF2E

Flexible High Bay



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-HBF2E	100-277V	14°F – 113°F -10°C – 45°C	50,000 HOURS	3000K, 4000K, 5000K, 6000K	80+	120 lm/W

MODEL	POWER (W)	NUMBER OF SEGMENTS	LUMENS (lm) ±10%	EFFICACY (lm/W)
2-45W	45	3	5,400	120
2-75W	75	5	9,000	120
2-105W	105	7	12,600	120
4-90W	90	3	10,800	120
4-150W	150	5	18,000	120
4-210W	210	7	25,200	120

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT	WEIGHT
2-45W	23.6 in 600 mm	7.6 in / 192 mm	1.5 in 37 mm	1.9 kg
2-75W		13.4 in / 340 mm		2.7 kg
2-105W		19.2 in / 488 mm		3.7 kg
4-90W	47.2 in 1200 mm	7.6 in / 192 mm		3.1 kg
4-150W		13.4 in / 340 mm		4.9 kg
4-210W		19.2 in / 488 mm		6.8 kg

