

INTERIOR USL-ITRIF

Indirect Troffer



Interior Dimmable Warranty

OVERVIEW

This troffer features a modern design and transparent optics. The light source is transparent when off, and is edge-lit when on, creating a very minimalistic fixture.



FEATURES

- Edge-lit for indirect light
- Transparent when off
- 2x2 adjustable wattage model 30/35/40W
- 2x4 adjustable wattage model 30/40/50W
- 0-10V dimming
- Low glare



ORDERING INFORMATION

EXAMPLE PN: USL-ITRIF-2X4-60W-LV-40K-10V

USL-ITRIF	SIZE/POWER	VOLTAGE	CCT	DIMMING
	2X2-40W 2X2, 40 WATTS	LV 100-277V	30K 3000K	10V 0-10V DIMMING
	2X2-ADJ 2X2, ADJUSTABLE WATTAGE		35K 3500K	
	2X4-60W 2X4, 60 WATTS		40K 4000K	
	2X4-ADJ 2X4, ADJUSTABLE WATTAGE		50K 5000K	

INTERIOR USL-ITRIF Indirect Troffer



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-ITRIF	100-277V	50,000	3000K, 3500K 4000K, 5000K	80+	100 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)
USL-ITRIF-2X2-40W	40	4,000	100
USL-ITRIF-2X4-60W	60	6,000	100
USL-ITRIF-2X2-ADJ	30	3,000	100
	35	3,500	100
	40	4,000	100
USL-ITRIF-2X4-ADJ	30	3,000	100
	40	4,000	100
	50	5,000	100

DIMENSIONS

MODEL	L	W	H
USL-ITRIF-2X2	23.7 in 602 mm	23.7 in 602 mm	3.54 in 90 mm
USL-ITRIF-2X4	47.72 in 1212 mm		

