

EXTERIOR USL-VT1L Vapor Tight Linear Fixture



OVERVIEW

This linear fixture is vapor tight and has an optional motion sensor and emergency battery. It is suitable for use in parking garages, food processing facilities, and warehouses. The light source is removable for easy maintenance over the life of the fixture.

FEATURES

- IP66
- 0-10V dimming
- Emergency battery available on some models
- Motion sensor
- Vapor tight fixture
- Easy maintenance



ORDERING INFORMATION

EXAMPLE PN: USL-VTIL-4-80W-LV-40K-MS

USL-VTIL	SIZE / POWER*	VOLTAGE	CCT	OPTIONS*
	4-40W 4 FT, 40W	LV 100-277V	30K 3000K	0 NON-DIMMING
	4-40WH 4 FT, 40W, HIGH LUMENS		40K 4000K	10V 0-10V DIMMING
	4-60W 4 FT, 60W		50K 5000K	MS DIMMING WITH MOTION SENSOR
	4-80W 4 FT, 80W		60K 6000K	EM NON-DIMMING, EMERGENCY POWER
	4-80WH 4 FT, 80W, HIGH LUMENS			EMS DIMMING WITH MOTION SENSOR AND EMERGENCY POWER
	5-120W 5 FT, 120W			
	8-80W 8 FT, 80W			
	8-80WH 8 FT, 80W, HIGH LUMENS			
	8-120W 8 FT, 120W			
	8-120WH 8 FT, 120W, HIGH LUMENS			

*Note: Emergency power only available with 40W model. Motion sensor only available with 40W and 60W models.

EXTERIOR USL-VTIL Vapor Tight Linear Fixture



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-VTIL	100-277V	-4°F – 104°F -20°C – 40°C	50,000 HOURS	3000K, 4000K, 5000K, 6000K	83+	100-130 lm/W

MODEL	POWER (W)	LENGTH (ft)	LUMENS (lm) ±10%		EFFICACY (lm/W)	OPTIONS AVAILABLE	
			3000K	5000K		EMERGENCY POWER	MOTION SENSOR
USL-VTIL-4-40W	40	4	4,000	4,300	100-108	✓	✓
USL-VTIL-4-40WH			4,800	5,200	120-130	✓	✓
USL-VTIL-4-60W	60		6,600	7,200	110-120		✓
USL-VTIL-4-80W	80		8,000	8,400	100-105		
USL-VTIL-4-80WH			9,600	10,400	120-130		
USL-VTIL-5-120W	120		5	12,000	12,400	100-103	
USL-VTIL-8-80W	80	8	8,320	8,400	104-105		
USL-VTIL-8-80WH			10,000	10,400	125-130		
USL-VTIL-8-120W	120		12,480	12,600	104-105		
USL-VTIL-8-120WH			15,000	15,600	125-130		

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
4-FT 40W, 60W	47.8 in 1215 mm	4.6 in 116 mm	2.9 in 74 mm
4-FT 80W	50.2 in 1274 mm	5.5 in 140 mm	3.5 in 90 mm
5-FT 120W	62.0 in 1574 mm		
8-FT 80W, 120W	101 in 2570 mm	6.7 in 170 mm	4.1 in 105 mm

